

MSD Series

Manual Sidedrive Dual Mast Carton Sealer

The BestPack™ MSD Series is a Semi-Automatic Uniform Tape Carton Sealer and is our most popular operator-fed adjustable carton sealer. The MSD is a top of the line machine, designed to suit a variety of light-to-heavy duty uniform carton closure applications. Using side belt technology, the MSD will seal very narrow to wide cartons. Dual telescopic masts allow for an extra 4" carton height extension on the upper assembly.

Our MSD line incorporates our exclusive 2" or 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel.



Key Points of the Carton Sealer



Operator Fed



Uniform Cartons



Top & Bottom Seal

Features

- Two Belt Side Driven
- Telescopic Mast Design
- Extra 4" Carton Height Adjustment Available on Upper Assembly
- Adjustable Bed Height for: MSD22 & MSD32 - 23.5" to 30.0"
MSD23 & MSD33 - 25.75" to 30.0"
- Width/Height Adjustment either side of carton sealer
- Exclusive 4 Roller Upper Side Compression
- Tape Roll Lengths: 1000 yd., 1500yd., 2000yd.
- Heavy Duty Frame
- UL Approved Electrical Parts
- Capable of Interchanging 2" or 3" Tape Heads
- Electrical on/off box can be mounted on either side of carton sealer.

Options

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- 3 Flap Folder
- Motorized Height and/or Width Adjustment
- Heavy Duty Locking Casters
- Interlock Safety Gates
- Stainless Steel
- Infeed/Exit Conveyor w/L-Bracket Stabilizer

Extra Accessories to Improve Efficiency



Spare Parts Kit May Vary

Spare Parts Kit



Locking Casters



Long Infeed/Exit Conveyor
w/ L-Bracket Stabilizer



Spare Tape Head

- High Speed Motor Upgrade (Up to 125 ft. per min.)
- 3 Flap Folder
- Stainless Steel
- Short Infeed/Exit Conveyor w/L-Bracket Stabilizer
- Carton Sealing Tape

Machine & Carton Specifications

110 Volts 60 Hz
Power Requirements

Up to 40 Cartons/min.
Speed

None
Air Requirements

342-490 lbs
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
MSD22-2 2" Tape Head	(39.5") x (32.8") x (70.3")	(6.0" - U) x (4.25" - 20.0") x (3.5" - 20.5")	(23.5" - 30")	Up to 40	342
MSD22-3 3" Tape Head	(39.5") x (32.8") x (70.3")	(6.0" - U) x (5.25" - 20.0") x (3.5" - 20.5")	(23.5" - 30")	Up to 40	342
MSD22-6 6" Tape Head	(39.5") x (32.8") x (70.3")	(6.0" - U) x (8.25" - 20.0") x (3.5" - 20.5")	(23.5" - 30")	Up to 40	425
MSD23-2 2" Tape Head	(39.5") x (32.8") x (80.3")	(6.0" - U) x (4.25" - 20.0") x (3.9" - 30.0")	(25.8" - 30")	Up to 40	390
MSD23-3 3" Tape Head	(39.5") x (32.8") x (80.3")	(6.0" - U) x (5.25" - 20.0") x (3.9" - 30.0")	(25.8" - 30")	Up to 40	390
MSD32-2 2" Tape Head	(39.5") x (43.8") x (70.3")	(6.0" - U) x (4.25" - 30.0") x (3.5" - 20.5")	(23.5" - 30")	Up to 25	410
MSD32-3 3" Tape Head	(39.5") x (43.8") x (70.3")	(6.0" - U) x (5.25" - 30.0") x (3.5" - 20.5")	(23.5" - 30")	Up to 25	410
MSD33-2 2" Tape Head	(39.5") x (43.8") x (70.3")	(6.0" - U) x (5.25" - 30.0") x (3.9" - 30.0")	(25.8" - 30")	Up to 25	490
MSD33-3 3" Tape Head	(39.5") x (43.8") x (80.3")	(6.0" - U) x (5.25" - 30.0") x (3.9" - 30.0")	(25.8" - 30")	Up to 25	490

Information subject to change without notice.

*Outside Dimensions Only
U - Unlimited
All Models available in High Speed & Stainless Steel